

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture

Product name : Aerospray TB Reagent A: Carbol Fuchsin Decolorizer

Product code : SS-061A, SS-061A-EU, or SS-161A diluted with methanol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemical

#### 1.3. Details of the supplier of the safety data sheet

ELITechGroup Inc. 370 West 1700 South Logan, UT 84321 - USA

T+1 (435) 752-6011 - F+1 (435) 752-4127

qara\_ebs@elitechgroup.com - www.elitechgroup.com

#### 1.4. Emergency telephone number

Emergency number : Contact your distributor or poison control center in your country.

InfoTrac Emergency Response: Calls within the USA, phone: 1-800-535-5053. Calls outside the USA,

phone: +1 352-323-3500 (call collect)

Customer ID: #90104 (NOTE: this number is required when a customer calls into either phone number

above).

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flam. Liq. 2

Ox. Liq. 2

H272 - Highly flammable liquid and vapor
Ox. Liq. 2

H272 - May intensify fire; oxidizer

Met. Corr. 1

Acute Tox. 3 (Oral)

Acute Tox. 3 (Dermal)

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

Skin Corr. 1 H314 - Causes severe skin burns and eye damage

Acute Tox. 3 (Inhalation:vapour) H331 - Toxic if inhaled

STOT SE 1 H370 - Causes damage to organs (oral)

Full text of H statements : see section 16

#### 2.2. Label elements

#### **GHS US labeling**

Hazard pictograms (GHS US)



GHS03







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H272 - May intensify fire; oxidizer H290 - May be corrosive to metals

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H370 - Causes damage to organs (oral)

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.
P234 - Keep only in original container.
P242 - Use only non-sparking tools.
P260 - Do not breathe vapors, spray, mist.

P264 - Wash soap and water thoroughly after handling P270 - Do not eat, drink or smoke when using this product.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of soap and water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P312 - Call a doctor, a POISON CENTER if you feel unwell.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use ABC-powder, alcohol resistant foam, BC-powder, carbon dioxide (CO2),

D-powder to extinguish.

P390 - Absorb spillage to prevent material-damage. P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with

local, regional, national and/or international regulation.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
methanol	(CAS-No.) 67-56-1	85 – 100	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370
nitric acid	(CAS-No.) 7697-37-2	1-5	Ox. Liq. 2, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a doctor.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician

immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Call a physician immediately. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : ABC powder. Alcohol-resistant foam. BC powder. Carbon dioxide. Dry powder. Water spray. Foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor. May intensify fire; oxidizer.

Explosion hazard : May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed

containers, spreading fire and increasing risk of burns and injuries.

Reactivity : Highly flammable liquid and vapor. May intensify fire; oxidizer.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Prevent fire-fighting water from entering environment. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe

dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to

section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Hazardous waste due to

potential risk of explosion. May be corrosive to metals.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-

proof equipment. Wear personal protective equipment. Do not breathe

dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a

well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep away from ignition sources. Store in a well-ventilated

place. Keep cool. Keep container tightly closed. Store locked up. Store in corrosive resistant container

with a resistant inner liner. Keep only in original container.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources. Combustible materials. Metals.

SDS-00026C.docx Page 3 of 9 ©ELITechGroup Inc.
Release Date: 2021-11-22 US-EN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packaging materials : Store in corrosive resistant container with a resistant inner liner.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

nitric acid (7697-37-2)		
ACGIH	ACGIH TWA (ppm)	2 ppm
ACGIH	ACGIH STEL (ppm)	4 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; dental erosion
OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	2 ppm

#### 8.2. **Exposure controls**

**Boiling point** 

**Explosive properties** 

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves. Suitable gloves should be tested to EN 374. The glove material has to be

impermeable and resistant to the product/the substance/the preparation. As the product is a preparation of several substances, the resistance and penetration time/breakthrough time of the glove material cannot be calculated/observed in advance and, therefore, has to be checked prior to the application. The following are recommended: materials - natural latex or nitrile; thickness - 4 to 6 mils

(0.1 mm - 0.15 mm); minimum breakthrough time - 60 minutes.

Eye protection

Skin and body protection : Wear suitable protective clothing. Respiratory protection : Wear respiratory protection. Environmental exposure controls : Avoid release to the environment. Other information : Do not eat, drink or smoke during use.

: > 60 °C

#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties 9.1.

Physical state : Liquid Color : Colorless Odor : Characteristic : No data available Odor threshold

рΗ : 0.5

Melting point : Not applicable Freezing point : No data available

: 10 - 20 °C Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available : No data available

Oxidizing properties : May intensify fire; oxidizer.

Vapor pressure : No data available : No data available Relative density Relative vapor density at 20 °C : No data available

Solubility : Water: No data available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

#### 9.2. Other information

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Highly flammable liquid and vapor. May intensify fire; oxidizer.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong acids. Strong bases. metals. May be corrosive to metals. Combustible materials.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))
LC50 Inhalation - Rat	3.03 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	101.01 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3.03 mg/l/4h
ATE US (dust, mist)	3.03 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.

pH: 0.5

Serious eye damage/irritation : Assumed to cause serious eye damage

pH: 0.5

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

STOT-single exposure : Causes damage to organs (oral).

STOT-repeated exposure : Not classified

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

nitric acid (7697-37-2)	
NOAEL (oral,rat,90 days)	1500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation,rat,gas,90 days)	2.15 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

methanol (67-56-1)	
LC50 fish 1	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
nitric acid (7697-37-2)	
NOEC chronic fish	97.8 mg/l Test organisms (species): other:Amphiprion ocellaris (anemone fish) Duration: '3 mo'

#### 12.2. Persistence and degradability

Aerospray TB Reagent A: Carbol Fuchsin Decolorizer		
Persistence and degradability	Not established.	
methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance	
ThOD	1.5 g O <sub>2</sub> /g substance	
nitric acid (7697-37-2)		
Persistence and degradability	Not established.	

#### 12.3. **Bioaccumulative potential**

Aerospray TB Reagent A: Carbol Fuchsin Decolorizer		
Bioaccumulative potential	Not established.	
methanol (67-56-1)		
BCF fish 1	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
nitric acid (7697-37-2)		
Bioaccumulative potential	Not established.	

#### 12.4. Mobility in soil

methanol (67-56-1)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or

international regulation.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

#### **SECTION 14: Transport information**

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1230 Methanol, 3 (6.1), II

UN-No.(DOT) : UN1230 Proper Shipping Name (DOT) : Methanol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

: 3 - Flammable liquid Hazard labels (DOT) 6.1 - Poison



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

**DOT Symbols** : + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group, I - Proper shipping

name appropriate for international and domestic transportation

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). DOT Special Provisions (49 CFR 172.102)

Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1

bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail (49

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR : 60 L

175.75)

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger **DOT Vessel Stowage Location** vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one

passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which

the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

#### **Transportation of Dangerous Goods**

No additional information available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

UN-No. (IMDG) : 1230
Proper Shipping Name (IMDG) : METHANOL

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 1230
Proper Shipping Name (IATA) : Methanol

Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

methanol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Cont Subject to reporting requirements of United States SARA	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1%
nitric acid (7697-37-2)	
Listed on the United States TSCA (Toxic Substances Cont Subject to reporting requirements of United States SARA	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 313 - Emission Reporting	1%

### 15.2. International regulations

#### CANADA

methanol (67-56-1)	
Listed on the Canadian DSL (Domestic Substances List)	
nitric acid (7697-37-2)	

### **EU-Regulations**

No additional information available

### **National regulations**

methanol (67-	7-56-1)
Listed on EPA Ha	Hazardous Air Pollutant (HAPS)

#### 15.3. US State regulations

This product can expose you to methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

methanol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
U.S California - Proposition 65 - Other information		NSRL: 23,000 µg/day (oral); 47,000 µg/day (inhalation)		

methanol (67-56-1)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### nitric acid (7697-37-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

#### **SECTION 16: Other information**

Other information : None.

#### Full text of H-phrases:

•		
H225	Highly flammable liquid and vapor	
H272	May intensify fire; oxidizer	
H290	May be corrosive to metals	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H314	Causes severe skin burns and eye damage	
H331	Toxic if inhaled	
H370	Causes damage to organs	

SDS US Custom - EBS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Reason For Change: updated to latest GHS format and classifications to meet compliance. Added Prop 65 information to Section 15.